



# Submittal Form



## kwikSTIK® Paper Faced Metal Drywall Beads and Trims

### Product Benefits

Phillips kwikSTIK® Paper Faced Metal Drywall Beads and Trims are designed with ease of installation in mind. Phillips offers a large selection of these top quality products to finish any room. Phillips kwikSTIK® Paper Faced Products feature:

- No edge cracking. No nail pops with tape-on products.
- High strength proprietary paper prevents nose coat bleed-through and balling when sanding.
- No fasteners or nails needed for installation with tape-on products.
- Dimpled to help drying and serve as mud anchors.
- Proprietary paper composition promotes high wet and tear strength.
- Cuts down finishing time and requires less joint compound.
- Patented high strength paper with durable fibers for smooth consistent finishes with superior mud and paint adhesion.
- Extreme heat, cold and water tested for superior bond between steel and paper to eliminate delamination.
- Rust preventative fully galvanized coating to withstand elements and adverse drying conditions.

### Certification

All Phillips kwikSTIK® Paper Faced Metal Beads and Trims (with the exception of PSW, PST, PSN and PBS Southwestern types) meet or exceed ASTM C1047 Standard Specification for Accessories for Gypsum Wallboard.

### Lifetime Warranty

Phillips lifetime (30-year) warranty begins on the date of installation of the products in the building. Phillips kwikSTIK® tape-on products are manufactured to the highest industry standards and are warranted not to edge crack when installed to a stable structure using these standard installing techniques:

- Wallboard must be clean and dry before applying Phillips kwikSTIK® Paper Faced Products
- The kwikSTIK® steel core must completely cover all wallboard gaps
- Installation must provide a 1/4" gap between base of kwikSTIK® products and floor
- Full layer of taping joint compound must be applied between the wallboard and the kwikSTIK® products
- Primary coat must be completely dry before applying additional coats

Phillips will, at its option, replace the material or refund the purchase price if any edge cracking occurs. Phillips must be notified within thirty (30) days of edge crack discovery. Documentary evidence of installation date must be included with written notification to the following address:

Phillips Manufacturing Company  
Quality Control Department  
4949 S. 30<sup>th</sup> Street  
Omaha, NE 68107

Warranty does not extend to improper installation, horizontal application of inside offset corners, kwikSTIK® Paper Faced Nail-On products, destruction or damage to structure by misuse, abuse, casualty or act of nature.

### Veneer Plaster Application

Not recommended.

### Storage

Avoid bending or other damage and store in a dry place protected from moisture.

### Installation Recommendations

Phillips recommends installation in accordance with applicable ASTM standards and using prevalent industry standards. Phillips detailed installation recommendations are available at [www.phillipsmfg.com](http://www.phillipsmfg.com).

## Submittal Approvals:

**Job Name:** \_\_\_\_\_

**Contractor:** \_\_\_\_\_ **Date:** \_\_\_\_\_

The information and recommendations contained herein are, to the best of Phillips Manufacturing Company's knowledge and belief, accurate and reliable as of the date issued. Phillips Manufacturing Company has no control over the conditions of handling and use, and makes no warranty regarding the results obtained from the use of this data. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to determine that they are suitable and complete for its particular use. Phillips reserves the right to make alterations and amendments to the detailed specifications at its discretion. Phillips disclaims responsibility for all actions, proceedings, liabilities, claims, damages, cost, losses, and expenses in relation to, or arising out of, incorrect utilization of this information.