

kwikSTIK® Paper-Faced Tape-On Metal Corner Bead P1 XW EL (PEW)

kwikSTIK® Paper-Faced Tape-On Metal Corner Beads is used on 90° outside corners with any standard drywall thickness for straight, precise corners. The rigid steel-reinforced corner is covered with a unique, high strength paper providing maximum strength and protection while preventing cracking caused by the movement or shrinkage of framing members. Features over 50% thicker steel than ASTM C1047 minimum requirement and is installed by pressing firmly into joint compound and removing excess compound with a drywall knife or clean rag.




Product Data and Ordering Information

Material: .0.014 min thickness, minimum G40 galvanized
Part Number: PEW14EGB

| Length | Pieces Per Carton | Cartons Per Pallet | Feet Per Carton |
|--------|-------------------|--------------------|-----------------|
| 8" | 50 | 56 | 400 |
| 9' | 50 | 56 | 450 |
| 10' | 50 | 56 | 500 |

All Phillips products are made in the U.S.A.



Drawing not to scale

ASTM and Code Standards

All Phillips kwikSTIK® Paper-Faced Tape-On Metal Corner Beads meet or exceed the following ASTM standards:

- ASTM C1047 Standard Specification for Accessories for Gypsum Wallboard*
- ASTM A653 Standard Specification for Steel Sheet, Zinc-Coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvannealed) by the Hot-Dip Process

SDS and other technical information available at www.phillipsmfg.com.

Patents

U.S. Patents 6,295,776; 6,539,680; 6,722,092 and 7,013,610

Leed Credits for Recycled Content

MR2 – The steel and vinyl used in Phillips Manufacturing products is 100% recyclable.

MR4 – Phillips Manufacturing steel and vinyl products have a minimum of:

| | |
|---------------------------------|-----|
| Total recycled content: | 30% |
| Post-consumer recycled content: | 25% |
| Pre-consumer recycled content: | 5% |

Storage

Avoid bending or other damage and store in a dry place protected from moisture.