

1/2" J-Weep

J-Weep is a versatile product used in several applications. The punched weep holes allow for usage as a sill weep screed in exterior stucco applications. Perforated flanges aid attachment and plaster keying and the 3-1/2" nailing flange meet applicable code requirements.

Product Data and Ordering Information

Material: 0.018" min thickness, galvanized steel
Part Number: JW5HDG

Length	Pieces Per Bundle	Cartons Per Pallet	Feet Per Bundle
10	10	50	100

Made in U.S.A. with domestic or imported ingredients

ASTM and Code Standards

All Phillips J-Weep products meet or exceed the following ASTM standards:

- ASTM C1861 - Standard Specification for Lathing and Furring Accessories, and Fasteners, for Interior and Exterior Portland Cement-Based Plaster.
- ASTM A653 - Standard Specification for Steel Sheet, Zinc-Coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvannealed) by the Hot-Dip Process

Phillips Manufacturing recommends installation to the following ASTM standard:

- ASTM C1063 Installation of Lathing and Furring to Receive Interior and Exterior Portland Cement-Based Plaster

SDS and other technical information are available at www.phillipsmfg.com

Leed Credits for Recycled Content

MR2 – The steel and vinyl used in Phillips Manufacturing products is 100% recyclable.

MR4 – Phillips Manufacturing steel and vinyl products have a minimum of:

Total recycled content:	30%
Post-consumer recycled content:	25%
Pre-consumer recycled content:	5%

Storage

Avoid bending or other damage and store in a dry place protected from moisture.

Leed v4 for building and Design Construction

- MR Prerequisite: Construction and Demolition Waste Management Planning.
- MR Credit: Construction and Demolition Waste Management.
- MR Credit: Building Product Disclosure and Optimization Sourcing of Raw Materials, Option2.
- MR Credit: Building Product Disclosure and Optimization Environmental Product Declaration, Options 1 & 2.
- MR Credit: Building Product Disclosure and Optimization Material Ingredients, Option 1.
- MR Credit: Building Life-Cycle Impact Reduction, Option 4

